## **PCT**





## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:

B60T 8/18

(11) International Publication Number: WO 00/41922

(43) International Publication Date: 20 July 2000 (20.07.00)

GB

(21) International Application Number: PCT/GB00/00089

(22) International Filing Date: 14 January 2000 (14.01.00)

15 January 1999 (15.01.99)

14 January 2000 (14.01.00)

(71) Applicant (for all designated States except US): GLIDE-RITE PRODUCTS LIMITED [GB/GB]; Mill Lane, Passfield, Liphook, Hampshire GU30 7RP (GB).

(72) Inventor; and

(30) Priority Data:

9900968.0


(75) Inventor/Applicant (for US only): GLAZIER, Mark [GB/GB]; Magnolia Cottage, Coombe Road, Hillbrow, Liss, Hampshire GU33 7NU (GB).

(74) Agents: BERESFORD, Keith, Denis, Lewis et al.; Beresford & Co., 2-5 Warwick Court, High Holborn, London WC1R 5DJ (GB). (81) Designated States: AU, CA, NZ, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: LOAD SENSING SYSTEM



(57) Abstract

There is described a vehicle having a body suspended on one or more axles by means of gas-filled suspension units (4), the vehicle being provided with means (3) to vary the pressure within the suspension units to control the spacing between the body and the axle or axles and a braking system supplying a brake fluid to braking actuators (14) operable to brake the vehicle's wheels, and further comprising a load sensing valve (13, 35) operable to apply a variable throttling effect to impede the flow of brake fluid to the braking actuators, characterised in that the throttling effect of the load sensing valve is varied by a control means (25-28,31) responsive to the pressure within the gas-filled suspension units.